




HOT WATER STORAGE TANKS

TECHNICAL DATA

Model	...	BC 200K60	BC 300K	BC 500K80	BC 750K	BC 1000K	BC 1500F	BC 2000F
Volume group	...	200	300	500	750	1000	1500	2000
Energy efficiency class	...	B	B	B	-	-	-	-
Standing loss heat	W	53	50	73	54	77	158	186
Rated pressure	MPa	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Volume	L	193	272	491	748	961	1471	2000
Insulation thickness	mm	75	85	80	125	125	100	100
Gross weight	kg	53	64	112	172	196	278	322
Insulation type		Rigid foam	Rigid foam	Rigid foam	Rigid foam	Rigid foam	EPS	EPS

CONNECTIONS

1: Inlet / Outlet		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G2 F	G2 F
5: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F
6: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G3/4 F	G3/4 F	G1 1/4 F	G1 1/4 F	G1 1/4 F	G2 F	G2 F

DIMENSIONS

A	mm	200	205	220	330	330	385	395
C	mm	855	835	980	880	1050	1220	1230
D	mm	600	670	800	1100	1100	1250	1400
F	mm	515	575	635	645	760	845	855
G	mm	75	85	80	125	125	100	100
H	mm	1430	1605	1765	1675	2020	2210	2255
K	mm	855	945	1045	960	1190	1305	1315
L	mm	1180	1315	1460	1270	1620	1765	1775